



## MINI OTDR Multimode Touchscreen OTDR - OLS - OPM - VFL- RJ45 Tester

### TECHNICAL FEATURES


General Specifications	
<b>Display</b>	4,3 inches 800 x 480 IPS TFT – LCD capacitive touch screen
<b>Power Supply</b>	Polymer Li-Battery: 3.7V, 4000mAh Adapter: 5VDC, 2A
<b>Battery working</b>	Standby>20h; Continuous test>12h
<b>Data Storage</b>	Internal storage: 8GB, ≥20 thousand curves
<b>Data Interface</b>	USB Type-C Bluetooth Android APP for Remote Management and reporting
<b>Working Temperature</b>	-10° C~50° C
<b>Storage Temperature</b>	-40° C~ 70° C
<b>Relative Humidity</b>	0~95% Non-Condensing
<b>Weight</b>	≤400g (Battery included)
<b>Size</b>	174mm x 92mm x 45mm

OPM ,LS Specification and RJ45 cable tester	
<b>Wavelength Range</b>	850nm~1700nm
<b>Test Range</b>	-70dBm~+10dBm (optional) -50dBm~+26dBm (Standard)
<b>Resolution</b>	0.01dB
<b>Uncertainty</b>	±5%
<b>Frequency Identification</b>	CW/270/330/1k/2kHz
<b>LS Wavelength</b>	Consistent with OTDR
<b>Output Power</b>	≥-5dBm
<b>Stability</b>	CW, ±0.5dB 15min (After 15min of preheating)
<b>Connector</b>	SC/UPC or SC/APC (see ordering guide)
<b>Mode</b>	CW/270/330/1k/2kHz
<b>RJ45 Cable tester distance</b>	Max 300m

OTDR Specifications	
<b>Model</b>	M1
<b>Wavelength</b>	850/1300nm
<b>Fiber Type</b>	G.652D
<b>Dynamic Range</b>	22/24dB
<b>Event Blind Zone</b>	1.5m
<b>ATT Blind Zone</b>	8m
<b>Test Range</b>	Max 7/48km
<b>Pulse Width</b>	3ns~20us
<b>Ranging accuracy</b>	±1m+ Sampling interval +0.005% x Test distance
<b>Linearity</b>	±0.05dB/dB
<b>Max Sample Points</b>	≥20000
<b>Max Sample Resolution</b>	≤0.03m
<b>Sampling Resolution</b>	0.05m~8m
<b>Loss Resolution</b>	0.01dB
<b>Loss Threshold</b>	0.20dB
<b>Range Resolution</b>	0.01m
<b>File Format</b>	SOR Standard File Format
<b>Laser Safety Level</b>	Class II

VFL Specification	
<b>Wavelength</b>	650nm±20nm
<b>Output Power</b>	≥10mW
<b>Mode</b>	CW/1Hz/2Hz
<b>Connector</b>	Universal FC/SC/ST

### ORDERING GUIDE



The information given herein, including drawings, illustrations and schematics are intended for illustration purposes only and is believed to be reliable. However, HAR&CA makes no warranties to its accuracy or completeness and disclaims any liability in connection with its use. HAR&CA obligations shall be only set forth in HAR&CA standard terms and conditions of the sale and in no case, HAR&CA be liable for any incidental, indirect or consequential damages arising out of sale, resale, use or misuse of the product. Users of HAR&CA products should make their own evaluation to determine the suitability of such each product for the specific application.