



HAR&CA



HC-V9m

OPTICAL CORE ALIGNMENT FUSION SPLICER

- 6 MOTORS
- STABLE
- RELIABLE
- FAST

Priority model for backbone project and maintenance

MAIN FEATURES

DACAS-Digital Analysis Core Alignment Systems

German CNC technique and integrated fiber-adjust frame, which make performance much stable

Fiber type identification function

V-groove precise alignment, high quality and low loss

Auto-splicing mode, using friendly design

Dust-proof, water-proof, high-temperature resistance.adapting to various altitude and harsh environment

4.3" high resolution color LCD touch screen, 480X magnification, visible clearly with bare eyes


Packed with detachable 5200mAh battery, more than 250 times of splicing and heating

3 high-power white LEDs and illuminated keypads simplifies your work at night

Detachable multifunction fixture, suitable for various fiber type

Built -in Japanese components and Korean chipset


Optical imaging system ranks No. 1 in the world



HIGH-POWER WHITE LEDS



4.3" TOUCH SCREEN



FIBER ENDFACE MELTER & FUSION SPLICER 2 IN 1

The information given herein, including drawings, illustrations and schematics are intended for illustration purposes only and is believed to be reliable. However, HAR&CA makes no warranties to its accuracy or completeness and disclaims any liability in connection with its use. HAR&CA obligations shall be only set forth in HAR&CA standard terms and conditions of the sale and in no case, HAR&CA be liable for any incidental, indirect or consequential damages arising out of sale, resale, use or misuse of the product. Users of HAR&CA products should make their own evaluation to determine the suitability of such each product for the specific application.


H-DS-2024-FUSION SPICER HC-V9m_EN_Rev01

www.hareca.it

EQUIPMENT PARAMETERS

MODEL	V9 Mini
DIMENSION	135W*160L*135H (excluding rubber bumper)/ 140W*165L *135H (including rubber bumper)
WEIGHT	2250G(with battery)/ 1870G (without battery)
NUMBER OF FIBER	Single
APPLICABLE FIBERS	SM(ITU-T G.652& G.657)/MM(ITU-T G.651)/DS(ITU-T G.653)/NZDS(ITU-T G.655)
COMPATIBLE FIBER/CABLE	0.25 - 3 0mm/Indoor Cable
CLEAVED LENGTH	DIAMETER 0.125 -1 mm/Cleave Length: 8-16mm
CLADDING DIAMETER	80 - 150µm
SPLICING MODE	Pre-set 41 splicing modes, max 100 modes
HEATING MODE	Pre-set 5 heating modes (20/30/40/50/60mm), max 100 modes
TYPICAL SPLICE LOSS	SM 0.02dB / MM 0.01 dB/ DS: 0.04dB / NZDS 0.04 dB/ G.657 0.02dB (ITU-T Standard)
RETURN LOSS	≥ 60dB
LIGHTING	3 White LEDs
SPLICING TIME	Quick mode: 6s
ESTIMATED SPLICE LOSS	Available
HEATING SLEEVE LENGT	20 - 60 mm
HEATING TIME	Quick heating time: 13s, typical heating time: 30s
RESULTS STORAGE	20000 latest records & 200 images
TENSION TEST	1.96 - 2.25N
OPERATING CONDITION	Operating Altitude: 0 - 5000m above sea level, 0 - 95% relative humidity, - 10 - 50 °C, Max Wind 1 Sm/s
STORAGE CONDITION	0 ~ 95% relative humidity, -40 - 80°C
DISPLAY	90° bi-directional view, 4.3" Colar High Resolution Display
FIBER VIEW & MAGNIFICATION	X, Y, XY, X/Y 480X Magnification
POWER SUPPLY	AC Input 100 - 240V, DC Input 12 - 1 SV
NO. OF SPLICE/HEATING WITH BATTERY	5200mAh Battery Capacity, Typical 250 times (Splice + Heat)
OPERATING METHODS	Button/rouch Screen
AUTOMATIC CALIBRATION	Automatic arc calibration by air pressure and temperature
ELECTRODE LIFE	5000 arcs
TERMINAL	Mini USB 2.0

STANDARD ACCESSORIES

NAME	QUANTITY
FUSION SPLICER V9MINI 	1 pcs
FIBER CLEAVER	1 pcs
BATTERY	1 pcs
POWER ADAPTER	1 pcs
AC POWER LINE	1 pcs
BACK-UP ELECTRODE	1 pcs
COOLING TRAY	1 pcs
CARRYING CASE	1 pcs
CARRYING STRAP	1 pcs
USER MANUAL	1 pcs
SPLICING TEST REPORT	1 pcs
FIBER STRIPPER	1 pcs
DROP CABLE STRIPPER	1 pcs
ALCOHOL BOTTLE	1 pcs



The information given herein, including drawings, illustrations and schematics are intended for illustration purposes only and is believed to be reliable. However, HAR&CA makes no warranties to its accuracy or completeness and disclaims any liability in connection with its use. HAR&CA obligations shall be only set forth in HAR&CA standard terms and conditions of the sale and in no case, HAR&CA be liable for any incidental, indirect or consequential damages arising out of sale, resale, use or misuse of the product. Users of HAR&CA products should make their own evaluation to determine the suitability of such each product for the specific application.